

PORT TARANAKI

Lifting capability

As a fully operational deep water port, Port Taranaki has modern plant and equipment, and skilled, experienced staff to service all customer needs.

For your lifting requirements, on-site we have two Liebherr LHM 400 mobile cranes and two reach stackers.

Liebherr LHM 400 mobile cranes


Our two LHM 400 mobile cranes are capable of a wide variety of tasks, and our expert, experienced staff can perform single and double lifts.

Each LHM 400 has an outreach of 48 metres and a lifting capacity of 104 tonnes at 22 metres.

Each crane is fitted with a motorised hook. This can be changed out for a Bromma spreader for lifting containers, or for specialised equipment to operate grabs or lift project cargo.

Liebherr capacity charts

Radius (metres)	Capacity (metric tonnes)	Radius (metres)	Capacity (metric tonnes)
10	104.0	35	59.1
22	104.0	36	56.8
23	99.9	37	54.6
24	95.0	38	52.8
25	90.4	39	50.9
26	86.3	40	49.3
27	82.5	41	47.6
28	79.0	42	45.9
29	75.1	43	44.6
30	72.2	44	43.1
31	68.9	45	41.7
32	66.3	46	40.4
33	63.9	47	39.1
34	61.2	48	37.9



Making *trade* easy



Permissible capacities

Hook operation **normal** duty: 52,0 tonnes capacity SWL

Hook operation **heavy** duty: 104,0 tonnes capacity SWL

How can we help you?

We have the tools, skills and expertise to safely execute complex lifts - whether that be on land or to and from vessels. We also provide lift plans authorised by a chartered engineer.



Load capacity



Extensive heavy lift plans



Flexible cranes - a variety of spreaders and rigging gear



Three experienced operators

Contact:

Ross Dingle

Head of Commercial

M: +64 27 310 5112

E: rdingle@porttaranaki.co.nz





Hyster reach stacker



Fantuzzi reach stacker

Designed for fast handling of containers and loads, our two reach stackers are agile and flexible, and fitted with spreaders that can be used to transport project cargo and even small vessels.

Hyster capacity chart

	9'6" - _____ 8'6" - 31.0t 8'0" - 31.0t	9'6" - 43.0t 8'6" - 45.0t 8'0" - 45.0t
9'6" - _____ 8'6" - 16.0t 8'0" - 16.0t	9'6" - 31.0t 8'6" - 31.0t 8'0" - 31.0t	9'6" - 45.0t 8'6" - 45.0t 8'0" - 45.0t
9'6" - 16.0t 8'6" - 16.0t 8'0" - 16.0t	9'6" - 31.0t 8'6" - 31.0t 8'0" - 31.0t	9'6" - 45.0t 8'6" - 45.0t 8'0" - 45.0t
9'6" - 16.0t 8'6" - 16.0t 8'0" - 16.0t	9'6" - 31.0t 8'6" - 31.0t 8'0" - 31.0t	9'6" - 45.0t 8'6" - 45.0t 8'0" - 45.0t
9'6" - 16.0t 8'6" - 16.0t 8'0" - 16.0t	9'6" - 31.0t 8'6" - 31.0t 8'0" - 31.0t	9'6" - 45.0t 8'6" - 45.0t 8'0" - 45.0t

